

CONNECTOR FOR ELECTROCHEMICAL SENSORS TYPE AC2

Type: KA2C.*

Description

The connector enables the use of the biosensor based on the substrates AC2, in classical electrochemical arrangement with stirred vessel. The cell TC4, TC5, TC6 is recommended for use with KA2C.*.



Physical parameters

Dimensions:

Weight: 36 gms
 Length: 37 mm
 Width: 10 mm

Types of termination

Model	Cable	Termination	Evaluating Units
KA2C.S	Three core Shielded cable	Single conductors	any device
KA2C.1	Three core Shielded cable	Banana plugs	any device
KA2C.2	Three core Shielded cable	7 poles BVT connector	any device
KA2C.3	Three core Shielded cable	Triad01 Palminstruments	Palmsens - Palminstruments
KA2C.4	Three core Shielded cable	BNC connectors	eDAQ
KA2C.5	Three core Shielded cable	Small banana plugs	any device

Ordering Information

- The order is specified by whole product code
- Minimum order quantity - 1 connector
- Delivery time for standard KA2C connector is 4 weeks from receipt of order
- Delivery time for non-standard KA2C connector depends on final technical specification of order

Recommended Vessel

- TC4, TC5, TC6

Example of Order

- 5 pieces - KA2C.S